

# **GREASE PUMP SEPARATED AIR MOTOR 60:1 1000 GR/MIN 180 KG**



Part No  
**12652**

## TECHNICAL DATA





### GREASE PUMP SEPARATED AIR MOTOR 60:1 1000 GR/MIN 180 KG

Air Operated Grease Pump. With separated air motor from the pump tube. Avoid "sticky" grease to enter into the air motor. For both mobile and fixed installations.. Bung adapter G 2" (part No 28591) included. We recommend air lubricators when using a pump with divorced air motor.

#### TECHNICAL DATA

Part No	12652
Ratio	60:1
Capacity	1000 gr/min
For container	180 kg
Air connection	1/4" (F) BSP
Maximum air pressure	1 (10) MPa (bar)
Recommended air pressure	0,4 (4) - 0,7 (7) MPa (bar)
Outlet	3/8" (F) BSP
Pump tube	930 mm
Length	1370 mm
H.S. Code	84135069

## RELATED PRODUCTS

PART NO	DESCRIPTION	
18573	Follower plate 180 kg 560-590 mm	
29057	Dust cover for drum adapter	
99601	Installation kit grease for 180 kg drums. (127 series) (pump not included)	
1125372	Inlet strainer for grease pumps.	
18542	Drum cover 180 kg 560-605 mm	