

# **GREASE PUMP SEPARATED AIR MOTOR 60:1 1000 GR/MIN 12- 20 KG**



Part No  
**12650**

## TECHNICAL DATA




### GREASE PUMP SEPARATED AIR MOTOR 60:1 1000 GR/MIN 12- 20 KG

Special version for "sticky" greases . For both mobile and fixed installations. Bung adapter G 2" (part No 28591) included. We recommend air lubricators when using a pump with divorced air motor.

#### TECHNICAL DATA

Part No	12650
Ratio	60:1
Capacity	1000 gr/min
For container	12- 20 kg
Air connection	1/4" (F) BSP
Maximum air pressure	1 (10) MPa (bar)
Recommended air pressure	0,4 (4) - 0,7 (7) MPa (bar)
Outlet	3/8" (F) BSP
Pump tube	450 mm
Length	890 mm
H.S. Code	84135069

**RELATED PRODUCTS**

PART NO	DESCRIPTION	
18544	Drum cover 12,5-20 kg 275-305 mm	
18570	Follower plate 18-20 kg 265-290 mm	
18569	Follower plate 12,5 kg 230-260 mm	
1125372	Inlet strainer for grease pumps.	
99604	Installation kit grease for 20 kg drums (127 series) (pump not included)	
18545	Drum cover 18-20 kg 290-327 mm	
29057	Dust cover for drum adapter	