

DIGITAL HAND METER PRE-SET

DIGITAL HANDMÄTARE FÖRINSTÄLLBAR



Part No. / Art. Nr.:
20400, 20422, 20452, 20471, 20472, 20491

GENERAL

EN

Digital pre-set oil meter, featuring a mechanism which, when activated, automatically shuts off the valve when the desired volume is reached.






- Simply and intuitive to use, it has a large display with 6 buttons
- Ergonomic four finger trigger with lock function
- Powered by 4 AA-batteries
- Light and robust, handle is made of cast aluminium and the display is surrounded by shock resistant TPE
- Several models with different outlets available to suit every application

ALLMÄNT

SE

Digital förinställbar oljemätare, med en mekanism som när den aktiveras, automatiskt stänger ventilen när önskad volym uppnås. Kan användas för olja och glykol.

- Enkel och intuitiv att använda, stor display med sex knappar
- Ergonomisk avtryckare med spärrfunktion
- Drivs av 4st AA-batterier
- Lätt och robust, handtag i gjuten aluminium och displayen är omgiven av stöttålig TPE
- Flera modeller med olika utlopp för att passa alla applikationer

MODEL OVERVIEW	PART NO / ART.NR.	OUTLET TYPE	UTLOPP	EN	SE
	20422	Malleable hose, manual non-drip	Formbar slang, manuell non-drip		
	20452	60° rigid, manual non-drip	60° rör, manuell non-drip		
	20471	90° hose, automatic non-drip	90° slang, automatisk non-drip		
	20472	90° hose, manual non-drip	90° hose, manual non-drip		
	20491	135° hose, automatic non-drip	135° slang, automatisk non-drip		

TECHNICAL DATA	EN
Inlet thread	1/2" BSP (F)
Wetted parts materials	Acetal, stainless steel, NBR, aluminum, brass, zinc plated steel
Meter type	Oval gear
Flowrate	1-30 l/min (0.25 - 7.5 US gal/min)
Maximum pressure	100 bar (1450 psi)
Temperature range	-10 a 50 °C (14 a 122 °F)
Accuracy (oil)	±0,5 %
Accuracy (coolant solutions)	±1 %
Viscosity range	Up to 2000 mPa.s
Display	LCD with double row digits
Units	Litres, gallons, quarts, pints
Batteries	4 x AA 1.5V
Weight (with nozzle and batteries)	2.1 kg (4.6 lb)
Dimensions (without outlet tube or nozzle)	297 x 89 x 155 mm (11.7" x 3.5" x 6.1") (length x width x height)

TEKNISKA DATA	SE
Inloppsgänga	1/2" BSP (Inv)
Material i kontakt med vätska	Acetal, rostfritt stål, NBR, aluminium, mässing, förzinkat stål
Typ av mätare	Ovalhjul
Flödes hastighet	1-30 l/min
Max arbetstryck	10,0 (100) MPa (bar)
Temperaturområde	-10 till 50 °C
Noggrannhet (olja)	±0,5 %
Noggrannhet (kylarvätska)	±1 %
Max viskositet	Upp till 2000 mPa.s
Display	LCD med dubbla rader
Enheter	Liter, gallon, quart, pint
Batterier	4 x AA 1.5V
Vikt (med utloppsslang och batterier)	2.1 kg (4.6 lb)
Mått (utan utloppsslang eller rör)	297 x 89 x 155 mm (längd x bredd x höjd)